

ASC-480PT723X-SS-WP (IN)



SPECIFICATIONS

- >> Built-in 23x AF zoom camera & Rx module
- >> Pan Speed Max. 17°/sec, 355° angle, Slow Scan (SS)
- >> Aluminum body & Polycarbonate smog dome cover
- >> Built-in Fan & Heater for outdoor condition
- >> Auto Pan
- >> Supports multiple protocol
- >> OSD Menu & Control
- >> Wall mount & in-ceiling mount available

>> Signal Format	NTSC, 525 lines	
>> Image Sensor	1/4" Sony Super HAD CCD	
>> Image Pixels	410K	
>> Horizontal Resolution	480 TV Lines	
>> Minimum Illumination	1.0 lux, (30IRE)	
>> Lens	Zoom Ratio	23x Optical Zoom 8x Digital Zoom
	Focal Length	f = 3.8~87.4mm
>> S/N Ratio	More than 49dB (AGC off)	
>> Pan	Angle	0° to 355°
	Manual Speed	Max. 17°/sec.
>> Tilt	Angle	0° to 90°
	Manual Speed	Max. 17°/sec.
>> ID (Camera Address)	0~225 address	
>> On-Screen Display	Camera ID (0~255)	
>> Auto Pan	1 Auto Pan (Zoom/Focus)	
>> Control	RS-485, baud rate: 2400/9600bps	
>> Power	AC 24V 50/60Hz 2A	
>> Operating Temperature	Indoor: -10°C to 50°C, Outdoor: -45°C to 60°C	
>> Humidity	0 to 90% RH (non-condensing)	
>> Dimensions / Weight	200(Ø) x 372(H)mm / 5kg	
>> Certification	CE, FCC, IP65	