



ASCENDENT proudly presents the VRD-Series Cameras (Vandal Resistant Domes)

Ascendent's NEW 530 line day/night vandal resistant dome (VRD) boasts a highly robust and extremely rugged cast aluminum and clear polycarbonate enclosure. Auto-iris and manual features make this camera a leader in the industry.

- >> Vandal proof dome camera (aluminum & PC)
- >> Built-in wide angle vari-focal lens (2.5-6mm, 4-9mm)
- >> High sensitive Super HAD Camera (0.3 Lx on standard resolution camera, 0.5 Lx on high resolution camera)
- >> Waterproof (IP67)
- >> DC Auto Iris Lens
- >> 12VDC/24VAC
- >> Heater kit included
- >> OSD (On-Screen-Display) Programming
- >> Day/Night
- >> Built-in heater/therm kit
- >> Dual voltage 24 VAC/12VDC

Ascendent's VRD Series offer the best in vandal resistant housings. Constructed of high impact aluminum and a high-quality optical polycarbonate dome enclosure, together with our 2.5 – 6mm / 4 – 9mm vari-focal lenses this is the ideal dome for interior or exterior applications. The camera's 3-axis Gimbal camera bracket allows for easy positioning and adjustment in ceiling and wall installations. The included surface mounting box provides NPT threaded openings to make surface or recessed conduit installations fast and easy.

The VRD Series is ideal for installations in prisons, schools, public transit areas, elevators and hallways. The standard 4-9mm varifocal lens, 530 lines of resolution, and 12VDC/24 VAC (included heater kit) combine to yield high quality images. These features, along with competitive pricing and the Sony CCD make the VRD Series the perfect choice for the serious Security Professional.

Ascendent Technology Group, a dynamic fast growing company, is committed to providing the CCTV industry with innovative and advanced products and technologies. With a singular commitment to the aggressive pursuit of product development and customer satisfaction, Ascendent continues to be an industry leader. Ascendent believes their sophisticated products provide simple solutions to the most complex security demands. We're proud to provide exceptional customer service and professional quality products.

VRD-Series Cameras



- >> Vandal proof dome camera (aluminum & PC)
- >> Built-in wide angle vari-focal lens (2.5-6mm, 4-9mm)
- >> High sensitive Super HAD Camera (0.3 Lx on standard resolution camera, 0.5 Lx on high resolution camera)
- >> Waterproof (IP67)
- >> DC Auto Iris Lens
- >> 12VDC/24VAC
- >> Heater kit included
- >> OSD (On-Screen-Display) Programming
- >> Day/Night
- >> Built-in heater/therm kit
- >> Dual voltage 24 VAC/12VDC

SPECIFICATIONS

>> Model Name	ASC-530VRD
>> Signal Format	NTSC
>> Image Sensor	1/3" Sony Super HAD CCD
>> Image Pixels	410K
>> Resolution	530+TVL
>> S/N Ratio	50 dB (AGC off)
>> DNR	Digital Noise Reduction reduces video noise
>> Minimum Illumination	Color 0.3lx @ F1.2, B/W 0.002lx (Sensor-Enabled)
>> Electronic Shutter	1/60 ~ 1/100,000 / Sec
>> Video Output Level	1.0 Vp-p (75 Ohm, Composite)
>> Lens	DC Auto Iris Lens 2.5 – 6.0 mm or 4.0 – 9.0 mm
>> Sync System	Internal / Line Lock
>> White Balance	ATW / Fast AWB / Manual
>> AGC	On / Off (programmable 6dB – 42dB)
>> BLC	Low/Med/High (programmable 0dB – 42dB)
>> Power Source	24VAC/12VDC dual voltage (auto sensing)
>> Temperature	-25C – 50C
>> Humidity	0 to 90% RH (non-condensing)
>> Construction	Body: Aluminum Diecasting Dome: Polycarbonate
>> Dimensions/Weight	100mm x 12mm / 1.4kg
>> Security Wrench	Security hex wrench included

ORDERING INFORMATION

ASC-530VRD256 | Vandal Resistant Dome Camera - 100mm, 530 line, 2.5-6mm, Internal Sync

ASC-530VRD49 | Vandal Resistant Dome Camera - 100mm, 530 line, 4-9mm, Internal Sync